Best Available Copy

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5: (11) International Publication Number: WO 91/0428 C08F 30/08, 230/08 A1 (43) International Publication Date: 4 April 1991 (04.04.9 C08J 3/28 PCT/US90/05032 (21) International Application Number: (74) Common Representative: CHANG, Sing-Hsiung: 6 Buc. skin Heights Dr., Danbury, CT 06811 (US). (22) International Filing Date: 7 September 1990 (07.09.90) (81) Designated States: AT, AT (European patent), AU, B. (European patent), BR, CA, CH, CH (European patent) (30) Priority data: 407,261 14 September 1989 (14.09.89) US DE*, DE (European patent)*, DK, DK (European pa 11 July 1990 (11.07.90) US tent), ES, ES (European patent), FI, FR (European pa 551,156

(60) Parent Applications or Grants (63) Related by Continuation

US 407,261 (CIP) 14 September 1989 (14.09.89) Filed on US 551,156 (CIP) Filed on 11 July 1990 (11.07.90)

(71)(72) Applicants and Inventors: CHANG, Sing-Hsiung [US/ US]; CHANG, Mei-Zyh [US/US]; 6 Buckskin Heights Dr., Danbury, CT 06811 (US).

Published

ŠU, US.

With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

tent), GB, GB (European patent), HU, IT (European patent), JP, KR, LU, LU (European patent), MC, NL, NI (European patent), NO, RO, SE, SE (European patent).

(54) Title: SOFT GAS PERMEABLE CONTACT LENS HAVING IMPROVED CLINICAL PERFORMANCE

James Barrell

化氯化钠 蛛经线 经货间运货 化

(57) Abstract

A hydrophilic soft gas permeable contact lens having substantially improved clinical performance by the provision of a sufficient higher proportion of hydroxy acrylic units to silicon units in the lens surface layer, as compared to that existing in the lens core, by the surface treatment of the lens, such as by reacting of the lens surface with polyols and base or acid or by radiation treatment of the base lens to graft, deposit or coat thereon hydroxy acrylic units.

DESIGNATIONS OF "DE"

Until further notice, any designation of "DE" in any international application whose international filing date is prior to October 3, 1990, shall have effect in the territory of the Federal Republic of Germany with the exception of the territory of the former German Democratic Republic.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

	•				
AT	Austria	es	Spain	MC	Monaco
AU	Australia	FI	Finland	MG	Madagascar
BB	Barbados	FR	France	ML	Mali
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Fasso	CB	United Kingdom	MW	Malawi
BG	Bulgaria	GR	Greuce	NL	Netherlands
BJ	Benin	HU	Hungary	NO	Norway
BR	Brazil	IT	ftaly	PL	Poland
CA	Canada	JP	Japan	RO	Romania
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
CG	Congo		of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CM	Cameroon	u	Liechtenstein	SU	Soviet Union
ЭO	Germany	LK	Sri Lanka	TD	Chad
DK	Denmark	LU	Luxembourg	TG	Togo
3**	_		•	US	United States of

SOFT GAS PERMEABLE CONTACT LENS HAVING IMPROVED CLINICAL PERFORMANCE

BACKGROUND OF THE INVENTION

This application is a continuation-in-part of prior applications, Serial Nos. 07/407,261, filed September 14, 1989; 07/132,174, filed December 14, 1987 (which in turn is a continuation-in-part of prior application Serial No. 001,149, filed January 7, 1987); and 07/381,587, filed July 18, 1989.

The present invention relates to contact lenses, and more particularly to hydrophilic soft gas permeable contact lenses having improved clinical performance.

and the second of the case of

in the friedrich of the training of the control of the first and the

Among the most important properties and requirements of contact lenses are substantial permeability to oxygen (commonly referred to as DK), and a highly wettable and deposition-resistant surface.

The development and use of plastic materials and compositions for contact lenses has been the subject of much attention over the years.

Among the first such developments was the so-called hard lens utilizing the hard plastic polymethylmethacry-late (PMMA). However, this material does not exhibit a significant degree of oxygen permeability and has very poor surface wettability characteristics. The art then progressed to soft lenses based upon poly 2-hydroxyethyl methacrylate (poly HEMA), a material having significantly better oxygen permeability and surface quality than the

hard PMMA plastic. Nevertheless, these characteristics were still not as high as desirable or necessary, and lenses of this type often resulted in serious problems of corneal staining, swelling, ulcers, thickness and infection.

Somewhat more recently, based upon better understanding of the corneal requirement of substantial oxygen permeability, the art proposed the use of so-called hard gas permeable (HGP) lenses composed of either of two types of plastic materials, acrylic silicone or acrylic fluorosilicone. See, e.g., U.S. Patent No. 3,808,178. ly, the oxygen permeability of HGP lenses can progressively be increased with increasing amounts of the silicone and/or fluorosilicone in the composition; at the same time, however, the surface wettability of the lens becomes progressively poorer. In order to overcome this problem, it is known to incorporate a relatively large amount of methacrylic acid (MAA), an ionic material, into the formulation, resulting in the lens surface being negatively charged to a certain extent. While this expedient does lead to improved surface wettability, the negativelycharged surface has a very high absorptivity leading to serious deposition problems. As a consequence, the HGP lens is of only limited potential. Appropriate design

Most recently, hydrophilic soft gas permeable (SGP) lenses have been developed based upon compositions containing, e.g., a polymerizable vinylic siloxane monomer and a hydrophilic vinylic monomer. See, e.g., U.S. Patent Nos. 4,136,250; 4,182,822; 4,261,875; 4,343,927; 4,426,389; 4,486,577; 4,605,712; 4,711,943 and 4,837,289. The SGP lenses of this type, which generally have a water content of from about 25 to 75% by weight, have excellent oxygen permeability and hydrophilicity. Surprisingly, however, the clinical performance of SGP lenses, including

functional (i.e., on the eye) wettability, deposition resistance, dehydration resistance and/or comfort, is very poor, making such lenses unsuitable for extended wear.

Thus, notwithstanding the advances made to date, there still exists a need for plastic contact lenses of the SGP type which not only possess a high degree of oxygen permeability, but also exhibit excellent clinical performance, such as functional wettability, deposition resistance, and comfort, thus making the lenses suitable for extended wear. The foregoing is the principal object of the invention.

SUMMARY OF THE INVENTION

This and other objects are achieved in the present invention by the provision of a soft gas permeable contact lens, composed of the polymerization product of compositions containing a polymerizable vinylic siloxane monomer and a hydrophilic vinylic monomer, having on the lens surface a proportion of hydroxy acrylic monomer units to silicon units sufficient to provide an SGP lens having the requisite high DK, softness and rebound elasticity, and which at the same time possess a high degree of clinical performance, thus rendering the lenses eminently suitable for long-term extended wear.

The requisite sufficient proportion of hydroxy acrylic monomer units to silicon units on the lens surface can be attained by surface treatment of the lens in order to increase hydroxy acrylic monomer units and/or to reduce the silicon units on the surface. In preferred embodiments of the invention, the surface treatment is carried out either by reaction on the lens surface with a polyhydric alcohol (polyol) and/or base or acid, or by radiation treatment of the lens to graft, deposit or coat hydroxy acrylic monomer units on the surface thereof.

It should be noted that the present invention differs significantly from prior art practices related to the provision, or attempted provision, of a hydrophilic surface on a hydrophobic lens. Thus, hydrophobic lenses are known in the art which are made of silicone rubber, a cross-linked polysiloxane, such as illustrated in U.S. Patent No. 3,228,741. These hydrophobic lenses are highly oxygen permeable but are extremely poor in functional wettability, deposition resistance and comfort, and also exhibit a mysterious tight lens syndrome. It is known in the art to seek to improve the functional wettability of such lenses by provision of an ultrathin coating of hydrophilic polymer. See, e.g., U.S. Patent Nos. 3,854,982; 3,916,033; 3,925,178; and 4,143,949. Generally these efforts have not in any event proven successful. reason is because the silicone rubber lens is rather rigid, and as a consequence an ultrathin (i.e., Angstoms level) hydrophilic coating is easily rubbed away during routine cleaning cycles, with the result that the lens soon re-exhibits the poor wettability, poor deposition resistance, discomfort and tight lens syndrome characteristic of silicone rubber hydrophobic lenses. Provision of thicker layers of hydrophilic polymer on the lens to resist rubbing off is impractical, since oxygen permeability of the lens is substantially reduced and since the differences between the refractive index of the silicone rubber and the thick hydrophilic polymer coating become such as to result in a highly undesirable lens.

In the present invention, the lens <u>per se</u> is a hydrophilic SGP lens containing a substantial amount of water (e.g., generally at least 25% by weight) such that its surface, in contrast to the silicone rubber lenses, is already highly hydrophilic and no apparent need would exist to provide a hydrophilic polymeric surface coating thereon as is taught with respect to hydrophobic lens

WO 91/04283 PCT/US90/05032

materials. In the present invention, it has surprisingly been found that the SGP lenses, even though having highly hydrophilic surfaces, nevertheless can still be very poor in clinical performance, and that this problem can be overcome by providing on the surface of the SGP lens a ratio of hydroxy acrylic units to silicon units which is sufficient to bring about significant clinical improvement.

Also in contrast with the treatment of hydrophobic silicone rubber lenses, it is found that the criteria employed in improving wettability of those lenses by hydrophilic monomer coatings is not correlatable to bringing about improved clinical performance in the hydrophilic SGP lenses to which the present invention is directed. For example, for hydrophobic lenses, acceptable wettability has been determined based upon contact angle (see, e.g., Col. 7, lines 13-16, of U.S. Patent No. 4,143,949), resulting in findings that coatings based upon amide monomers (e.g., N-vinylpyrrolidone) are quite effective in improving wettability (see, e.g., Example 1-2 of the above patent). In contrast, however, in the context of the hydrophilic SGP lenses of the present invention and particular those of preferred center thickness of from 0.05 to 0.08 mm; such amide group-containing monomers are quite ineffective in improving the clinical performance of the SGP lenses.

Accordingly, the findings and techniques of the present invention would not have been derivable or predictable from the known practices regarding improving the wettability of hydrophobic silicone rubber lenses.

DETAILED DESCRIPTION OF THE INVENTION

The basic teachings and formulations and techniques regarding formation of silicone-based SGP lenses are known

in the art, as reflected in the earlier-mentioned patents, the disclosures of which are expressly incorporated herein by reference. The SGP lens is formed from the polymerization product of compositions containing at least one polymerizable vinylic siloxane (PVS) monomer, and at least one hydrophilic vinylic monomer. The polymerizable vinylic siloxane monomer contains at least one polymerizable vinylic group such as acrylic, styrenyl or vinylic group, at least one polysiloxanyl group, and at least one linkage connecting these two groups; thus, for example:

tris(trimethylsiloxy)silylpropyl-glycerol-ethyl methacrylate

7-tris(trimethylsiloxy)silylpropyl methacrylate (also sometimes referred to hereinafter as TSM)

Hydrophilic vinylic monomers suitable for use in SGP lens compositions along with the PVS include, for example, N,N-dimethylacrylamide (NNDMA), 2-hydroxyethyl methacrylate (HEMA), glyceryl methacrylate (GMA), N-vinyl pyrrolidone and the like.

The lenses <u>per se</u> are formed by lathe cutting, cast molding, spin casting, or other like known techniques.

The second of th

As earlier noted, SGP lenses made according to the known formulations possess a high oxygen permeability but exhibit poor clinical performance. In the present invention, it has been discovered that by increase of the

proportion of hydroxy acrylic monomer (HAM) units, preferably HEMA and/or GMA units, to silicon units at the lens surface, the clinical performance can be substantially improved. As used herein, the units referred to are the structural monomeric units or the number of silicon atoms, including those as part of an overall copolymeric structure.

Hydroxy acrylic monomer (HAM) suitable for the practice of this invention correspond to the formula

$$H_2C = C - C = O$$

wherein R is H or a substituted or unsubstituted alkyl, such as methyl or CH₂COOH; and X is a radical selected from the group consisting of hydroxyalkyloxy, hydroxyalkyl amine, and hydroxy; with the alkyl being substituted or unsubstituted, and preferably selected from C₁ to C₁₀ alkyls, most preferably C₂ and C₃ alkyls; and with the hydroxy on the alkyl being either a single hydroxy (e.g., as in 2-hydroxyethyl methacrylate) or multiple hydroxy (e.g., as in glyceryl methacrylate). Exemplary and preferred hydroxy acrylic monomers are:

- 1. 2-hydroxyethyl acrylate or methacrylate;
- 2. glyceryl acrylate or methacrylate;
- 3. ethylene glycolato ethyl acrylate or methacrylate, i.e., CH₂=CRCOO-CH₂-CH₂-O-CH₂-OH
 - 4. glycerolglyceryl acrylate or methacrylate, i.e., CH₂=CRCOO-CH₂CH(OH)-CH₂-O-CH₂-CH(OH)-CH₂-OH
 - 5. N-hydroxymethyl, N-methyl acrylamide or methacrylamide;
 - 6. N-2-hydroxyethyl, N-methyl acrylamide or methacrylamide;
 - 7. N-2,3-dihydroxypropyl, N-methyl acrylamide or methacrylamide;
 - 8. acrylic acid, methacrylic acid or itaconic

As noted, the SGP lens of the invention is made from the known SGP lens compositions and, after lens formation, the lens is then treated to provide on its surface a proportion of HAM units to silicon units (e.g., by increase of HAM units and/or by decrease of silicon units) sufficient to provide improved clinical performance of the lens, such as functional wettability, deposition resistance, dehydration resistance and comfort.

One means for achieving the requisite surface proportion of HAM to silicon units is by reaction of the lens surface, preferably in the dehydrated state, with a polyol of the formula R₁(OH)_n where R₁ is a substituted or unsubstituted alkyl, preferably a C_2 to C₅ alkyl, and n is an integer of at least 2, such as glyceryl methacrylate, ethylene glycol, glycerine, glycerine-glycerine, polyglycerine, or the like. reaction is preferably carried out in the presence of a base, such as sodium hydroxide, preferably in a concentration of 0.1 to 10 mole percent based on the polyol, or an acid or acid-containing mixture, such as ethanol/sulfuric acid, the reaction being conducted to the extent that the physical properties of the base lens (e.g., strength, oxygen permeability, softness, rebound elasticity, etc.) are essentially unaffected. reaction is intended to increase the HAM units in the surface layer by transesterification and/or to reduce the silicon units by the cleavage of siloxane bonds catalyzed by base or acid.

Alternatively, the core lens can be treated with a HAM, preferably 2-hydroxyethyl acrylate or methacrylate, by grafting, deposition or coating to the lens surface so as to provide a sufficient proportion of HAM units to silicon units at the lens surface. The grafting, deposition or coating can be carried out using known radiation-induced reactions, including reactions induced by UV,

 γ -ray, and other electromagnetic radiation, such as radio frequency, microwave and the like, electron beam radiation, including electrical discharge, and the like, with reactions induced by UV, Y-ray or electron beam radiation being preferred. The treating techniques per se that can be used in the practice of this invention are well known in the art, such as the grafting, deposition or coating cured by UV, Y-ray or electron beam, illustrated in U.S. Patent Nos. 3,916,033 and 3,854,982; coating by spin casting or cast molding of the lenses cured by radiation; or plasma treating techniques, such as those disclosed in U.S. Patent Nos. 3,925,178 and 4,143,949, as is well known in the art. The disclosures of these prior art patents are expressly incorporated herein by reference. In the preferred embodiment of the invention, the surface treatment produces on the lens surface a thin coating consisting essentially of poly(hydroxy alkyl acrylate and/or methacrylate), more preferably poly(2-hydroxyethyl acrylate and/or methacrylate).

34. 500000

The required sufficient proportion of HAM units to silicon units on the lens surface that produces the desirable clinical performance will vary primarily depending upon the type and amount of particular PVS and hydrophilic monomer employed. However, the sufficient proportion in the surface layer will, at any proportion, be higher than that existing in the lens body or core. Preferably, the proportion of HAM units to silicon units in the surface layer is at least 0.5. Generally, the higher the proportion the better the clinical performance of the lens, and the thicker the treated surface layer the better the durability of the lens wettability. However, the treated layer can not be so thick that the desired properties of the lens are adversely affected. The extent of acceptable surface treatment can be monitored by high resolution photoelectron spectroscopy (ESCA) or based on the clinical response as illustrated in the examples of this specificathe sufficient proportion of HAM units to silicon units on the lens surface can easily be determined by those skilled in the art.

Although not wishing to be bound by any theory as such, it is postulated that the improvement in the clinical performance of the lens comes about, at least in part. by virtue of establishment of compatibility between the delicate corneal wetting mechanism of the eye and the composition and structure of the lens surface. The known SGP lens having insufficient proportion of HAM units to silicon units or containing too high a level of silicon units on the surface are too hydrophobic for the spreading and binding of mucin to the lens surface. Mucin is the excellent wetting agent used in the cornea and contains a certain proportion of hydrophilic sites to hydrophobic sites. With increasing amount of HAM units on the lens surface, there are provided increased sites for hydrogen bonding with the hydrophilic sites on the mucin, while reduction of silicon surface units provides fewer hydrophobic sites and thus better spreading of mucin on the lens surface. As a consequence of the preferred embodiment of the invention herein, which results in the lens surface having a sufficient proportion of HAM units to silicon units, the lens surface becomes more closely matched to, and receptive to, tear mucin. As a result, the mucin can better spread on and bind to the lens surface so as to provide the improved clinical performance. Thus, when the wetting angle of the lens is controlled to that of the corneal surface free of mucin, the best results of this invention may result.

The invention is further illustrated with reference to the following examples.

EXAMPLE 1

SGP lenses were fabricated from buttons which were made according to the formulations and procedures set forth in U.S. Patent No. 4,182,822, the starting formulation consisting of 36% (by weight), Y-tris(trimethylsiloxy) silylpropyl methacrylate (TSM) prepared according to Example 1 of the above patent, 59% N,N-dimethylacrylamide (NNDMA), and 5% methyl methacrylate (MMA) with 0.3% t-butylperoxypyvalate included as a catalyst. The formulation was placed in a Teflon tube. After deoxygenation by nitrogen for 15 minutes, the tube was sealed and the formulation was polymerized in a 40°C water bath for six hours, followed by a 100°C treatment for another six hours. The buttons cut from the rods were post-cured at 110°C under high vacuum (0.5 Torr) for six hours.

The lens can be made by the lathe technique known in the art. The hydrated lenses were extracted and conditioned in physiological saline solution for a time sufficient to insure no substantial irritation.

医乳腺 医血液溶液 医多种基础 化氯化

The lens thus made has high DK, about 4 to 5 times higher than that of the conventional poly HEMA soft lens, and contains about 50% by weight of water, and thus has softness, rebound elasticity and a highly hydrophilic lens surface. The proportion HAM units to silicon units on the lens surface is equal to zero. Clinically, the lenses were very poor in performance such as functional wettability, deposition resistance and comfort, making the lens unsuitable for extended wear.

Provision of 6% by weight HEMA in the formulation, such that the formulation comprised 36% TSM, 58% NNDMA and 6% HEMA, results in a lens having high DK, softness, rebound elasticity, a highly hydrophilic surface and a

proportion of HAM to silicon units equal to 0.15, and thus an improved SGP lens having improved clinical performance, such as functional wettability, deposition resistance and comfort as compared to the control lens above. Clinically, the lenses could be worn for up to several hours by test patients.

In the same manner, using 20% by weight HEMA, such that the lens formulation contains 36% TSM, 44% NNDMA and 20% HEMA, results in a lens having high DK, softness, rebound elasticity, a highly hydrophilic surface and a proportion of HAM units to silicon units equal to 0.5, and thus even more improved clinical performance, such as functional wettability, deposition resistance and comfort, as compared to the control lens. Clinically, the lenses could be worn continuously for up to several days by test patients, with wettability marginally unacceptable in certain circumstances.

Further increase of the HAM to silicon proportion by increase of the amount of HEMA in the composition is at the expense of TSM, and thus reduces the oxygen permeability of the lens and/or causes the formation of opaque material. As shown in the following examples, further increase of the HAM to silicon proportion can be achieved by surface treatment.

EXAMPLE 2

The lens containing 20% HEMA as made in Example 1, after being hydrated in physiological saline solution, is then extracted in isopropanol for 24 hours, followed by treatment in the dry state with glycerine (96% purity, Colgate Palmolive Co.) containing 1 mole% NaOH at 70°C for 30 minutes by stirring. The strength of the lens after the treatment was not significantly affected. The resulting lens could be used for at least weekly extended wear

by the test patients. The clinical of long term wearing on one patient showed that the lenses could indeed continuously be worn for up to 3 months for at least certain patients. Thus, the surface treatment resulted in substantially improved clinical performance.

EXAMPLE 3

A SGP lens comprising 47% (by weight) TSM, 45% NNDMA and 8% HEMA, having 38% water content, high DK, softness, highly hydrophilic lens surface and a proportion of HAM units to silicon units equal to about 0.15, was found to be unsuitable for extended wear. Clinically, the lens produced poor vision, discomfort and encountered serious deposition-problems within less than four hours of wear. However, treatment of the same lens in dehydrated state by stirring the lens in a glycerine reagent (96% purity, Colgate Palmolive Co.) containing 10 mole% NaOH at 70°C for 2 hours converted the lens to one which on the same patient could be used for weekly extended wear for a three week testing period with stable vision and no observable deposition, and demonstrated a liquid layer over the lens surface.

EXAMPLE 4

and the second s

naka Barunar Kerilak dan 1946

According to an independent surface study (about 100 A° surface layer) by photoelectron spectroscopy (ESCA) analysis of the lens after being treated as described in Example 3 showed that there was a reduction of about 18% silicon or about 30% siloxy group and an increase of overall carbon content from 62.5 to 65% in which the C in the CO group increased from 10.5 to 12.5% and the C in the COOR group increased from 5.3 to 6.3% after the treatment. The increase of CO and COOR content should indicate that the transesterification of glycerine occurs, i.e., the

formation of glyceryl methacrylate. The reduction of silicon units and/or the increase of glyceryl methacrylate units after the treatment increases the proportion of HAM units to silicon units which provides the substantially improved clinical performance as described above. (Note: ESCA data is the average value of the treated surface with 100 A° depth. Thus, the value right at the surface is substantially higher than those reported above.)

EXAMPLE 5

An unhydrated optically polished lens button was made according to U.S. Patent No. 4,182,822 employing 36% (by weight) TSM, 42% NNDMA and 22% HEMA, and glycerine surface treated as set forth in Example 3 herein. The button was fully hydrated in physiological saline solution, and its surface was subjected to a number of simulated cleaning cycles, each cycle involving thumbrubbing 10 times in tap water, followed by wetting in physiological saline solution. The surface wettability to the physiological saline solution was substantially the same based on visual inspection after sixty (60) cleaning cycles, equivalent to about one years service life of the lens in weekly extended wear.

The surface of the untreated button was substantially not wettable by physiological saline solution under the same testing condition.

Although the invention has been described in connection with particular preferred embodiments, it is not intended to limit the invention to particular forms set forth, but on the contrary, it is intended to cover such alternatives, modifications and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims.

WHAT IS CLAIMED IS:

- 1. A hydrophilic soft gas permeable contact lens having high oxygen permeability, softness and rebound elasticity, comprised of a polymerization product of a composition comprising a polymerizable vinylic siloxane monomer and a hydrophilic vinylic monomer, and containing in its surface layer a sufficiently higher proportion of hydroxy acrylic monomer units to silicone units than exists in the lens body so as to additionally provide a high degree of clinical performance to said contact lens.
- 2. A contact lens according to claim 1, wherein said sufficiently higher proportion results from treatment of the surface of said lens so as to provide in said surface layer a sufficient proportion of hydroxy acrylic monomer units to silicon units.
- 3. A contact lens according to claim 2, wherein said hydroxy acrylic is hydroxyalkyl acrylate and/or methacrylate.
- 4. A contact lens according to claim 3, wherein said treatment comprises reaction of the lens surface with a polyol of the formula $R_1(OH)_n$, where R_1 is a substituted or unsubstituted alkyl, and n is an integer of at least 2.
 - 5. A contact lens according to claim 4, wherein said polyol is selected from the group consisting of ethylene glycol, glycerine, and mixture thereof.
 - 6. A contact lens according to claim 2, wherein said treatment comprises reacting onto said lens surface, by radiation-initiated reaction, hydroxy acrylic monomer.

- 7. A contact lens according to claim 6, wherein said hydroxy acrylic monomer is hydroxyalkyl acrylate and/or methacrylate.
- 8. A contact lens according to claim 7, wherein said radiation is electromagnetic radiation.
- 9. A contact lens according to claim 7, wherein said radiation is 8-ray or UV.
- 10. A contact lens according to claim 7, wherein said radiation is selected from the group consisting of electron beam, electrical discharge and radio frequency.
- 11. A contact lens according to claim 7, wherein said polymerizable vinylic siloxane monomer is *-tris(trimethylsiloxy)silylpropyl methacrylate and wherein said hydrophilic vinylic monomer is N,N-dimethylacrylamide.

12. A contact lens according to claim 3, wherein said hydroxyalkyl acrylate and/or methacrylate is selected from the group consisting of 2-hydroxyethyl methacrylate and glyceryl methacrylate.

m = 1 ... 1 (1797...

13. A contact lens according to claim 12, wherein said polymerizable vinylic siloxane monomer is δ -tris(trimethylsiloxy)silylpropyl methacrylate and wherein said hydrophilic vinylic monomer is N,N-dimethylacrylamide.

ರ್ಷ-ನಿರ್ದೇಶ್ವ ಸಹ್ಮರ ಕರ್ಮ ಹಲಕ್ಕೆಗಳ ಕರ್ಣದ ಸಹ್ಮಗಳ ಕರ್ಗಿಸುವ ಕರ್ಣಕ್ಕೆ

14. A contact lens according to claim 7 wherein said treatment produces on said lens surface a thin coating consisting essentially of poly(hydroxy alkyl acrylate and/or methacrylate).

State of the control of

- A contact lens according to claim 14 wherein said 15. poly(hydroxy alkyl acrylate and/or methacrylate) is poly (2-hydroxyethyl acrylate and/or methacrylate).
- A contact lens according to claim 11 wherein said 16. treatment produces on said lens surface a thin coating consisting essentially of poly(hydroxy alkyl acrylate and/or methacrylate).
- A contact lens according to claim 16 wherein said 17. poly(hydroxy alkyl acrylate and/or methacrylate) is poly(2-hydroxyalkyl acrylate and/or methacrylate).

n tropical de la companya del companya del companya de la companya

		International Application No	PCT/US90/05032
	SIFICATION OF SUBJECT MATTER (if several c		1
IPC	to international Patent Classification (IPC) or to both (5): CO8F: 30/08, 230/08; CO8J	7 3/28	384: 526/379
	S SEARCHED		
	Minimum Docu	mentation Searched 4	
Classificat	ion System i	Classification Symbols	
	264/1.1; 351/160H; 522	/99; 523/107	
U.S.	525/326.5, 384 526/27	9	
		er than Minimum Documentation into are Included in the Fields Searched !)
	MENTS CONSIDERED TO BE RELEVANT 14 Citation of Document, 14 with indication, where a	Taxanata of the relevant passages II	Relevant to Claim No. 15
ategory •			
7.	US, A. 4.099,859 (MERRIL see example II, III in pglycol.		1-10,13,1° 11-12
A	US, A, 4.259.467 (KEOGH 31 March 1981, see entir		1-17
Z	US, A, 4,260,725 (KEOGH 07 April 1981, see entir	1-3.12	
4	US, A, 4,487,905 (Mitche 11 December 1984, see en		1-17
4	US, A. 4,734,475 (GOLDEN) 29 March 1988, see entire		1-17
"A" docum conside	ategories of cited documents: 15 ent defining the general state of the art which is not are to be of particular relevance document but published on or after the international	"T" later document published after or priority date and not in conficited to understand the princip invention "X" document of particular relevan	ict with the application but lie or theory underlying the nea: the claimed invention
which i citation	ate ent which may throw doubts on priority claim(s) or is cited to establish the publication date of another or other special reason (as specified) ent referring to an oral disclosure, use, exhibition or	cannot be considered novel of involve an inventive step "Y" document of particular releval cannot be considered to involve document is combined with one	r cannot be considered to nce; the claimed invention an inventive step when the or more other such docu-
other m P" docume		ments, such combination being in the art. "4" document member of the same	Opious to a person skilled
CERTIFIC	CATION Itual Completion of the International Search 3	Date of Mailing of this International Sc	earch Report *
5 Nove	mber 1990	25 JAN 199	1
rnational S	earching Authority 4	Signature of Authorized Officer 10 Littà Euler Herbert J. Lilling	
JA7 UJ			

FURTHER INFORMATION CON	TINUED FROM THE SECOND SHEET	
A US, A, 4.7 25 October	80,510 (UEMIYA et al.) 1988, see entire document.	1-17
X US, A. 4.8 29 August	61.840 (LIM et al.) 1989. see column 4, line 41-	1-3,6-10, 14,15
A,P US, A, 4.9 24 April 1	20,184 (SCHÄFER et al.) 990, see entire document.	1-17
. OBSERVATIONS WHERE	CERTAIN CLAIMS WERE FOUND UNSEARCHABLE 1	
ments to such an extent that no	they relate to parts of the international application that do n meaningful international search can be carried out 1, specific they are dependent claims not drafted in accordance with the	cally:
PCT Rule 6.4(a).	man that an debat wast consist the primary of account to Aller a	to account and anno actioned of
	INITY OF INVENTION IS LACKING!	
is International Searching Authority	found multiple inventions in this international application as	follows:
As all required additional search of the international application.	fees were timely paid by the applicant, this international searc	th report covers all searchable claims
As only some of the required additional international internation	ditional search fees were timel, paid by the applicant, this in application for which fees were paid, specifically claims:	lernational seuts: raport covers only
The conviced additional coarse for		
	s were timely paid by the applicant Consequently this intern	national search report in contractor to
the invention first mentioned in the	s were timely paid by the applicant. Consequently, this intern ne claims; it is covered by claim numbers:	national search report is restricted to
As all searchable claims could be invite payment of any additional f	ie claims; it is covered by claim numbers: searched without effort justifying an additional fee, the Inter	. ••
As all searchable claims could be invite payment of any additional finance on Protest	ie claims; it is covered by claim numbers: searched without effort justifying an additional fee, the Inter	. ••